



visit our website

CUSTOMER BROCHURE



K-Series Transmitter

.....



.....

www.juukoitaly.it

K-series Features	1
Black Box	2
Automatic Channel Switching (ACS)	3
Multi-control System	3
Qi Wireless Charging Compatible	4
Data Feedback	4



Zero-G Safety	5
Dimensions	5
Technical Data	6
Accessories	7
Applications	9





K-Series Features

- Independent LEDs, indicate the status of the battery
- Activation of the transmitter is protected by an electronic key-code and an auto shut-off option which is programmable
- The system automatically change to another frequency in the presence of radio interference
- Eco power management system. Save on batteries
- It can receive and display via 4 LEDs signals coming from the receiver (relay action feedback)
- Mushrooms type EMO button
- Internal BootLoader, up firmware to the date by using computer
- Wireless pairing procedure using the keyboard pushbuttons
- Qi wireless charging pad is optional in New 2016 K plus series

Black Box

Track your crane or machine usage

With JUUKO Black Box function, you can always collect the usage data of both transmitter and receiver. This function is good for the hoist service and maintenance work, and also for those companies who provide lease or rent out service.

It is more than simple to see the usage data of both Transmitter and Receiver just by connect-ing the transmitter to the JUUKO's "Control pro" configuration software.

Line	Proportional	Other	Operation times Working hours	Operation times Working hours
X1	OK	OK	X13	OK
X2	OK	OK	X14	OK
X3	OK	OK	X15	OK
X4	OK	OK	X16	OK
X5	OK	OK	X17	OK
X6	OK	OK	X18	OK
X7	OK	OK	X19	OK
X8	OK	OK	X20	OK
X9	OK	OK	X21	OK
X10	OK	OK	X22	OK
X11	OK	OK	X23	OK
X12	OK	OK	X24	OK

Operation times	Working hours	Original	Working hours
Zero-g count	OK	User 1	OK
Stock-off count	OK	User 2	OK
Fib	OK	User 3	OK
Turn On	OK	User 4	OK
EMO	OK		




Automatic Channel Switching (ACS)

A system comes standard with a primary working frequency and a secondary working frequency. Automatic Channel Switching (ACS) allows continuous operation free from interference for the user. When radio interference occurs during normal operation, the radio communication automatically switch to the the secondary frequency.

- Bi-directional
- Safe communication
- Uninterrupted radio link benefits smooth operation

Multi-control System



Qi Wireless Charging Compatible

Charged and ready to go. Available as an option, the main Wireless "Qi" charging standard has been adopted by hundreds of leading manufacturers and introduces the convenience of charging your device without using cables but simply by placing it on its Charging Pad.

Data Feedback

The "Data Feedback" function enables the visualization of status through 4 LEDs. These 4 LEDs are programmable to see the actual STATUS of each relay in receiver.



Zero-G Safety

The zero-g safety function can prevent the uncontrolled output of commands in specific emergencies.

The G sensor can detect if the transmitter receives a hard impact, dropped or thrown. These features can deactivate either the complete radio system or only the safety-relevant function relays.

Dimensions



JK1616	JK1212	JK1010	JK808	JK606	JK404	JK202
290*57*51	JK1200	JK1000	JK800	JK600	JK400	JK200
449g	242*57*51	242*57*51	193*57*51	193*57*51	193*57*51	193*57*51
	389g	389g	325g	325g	325g	325g

JK1616 model is only available with double step push-buttons and Qi inductive battery charger

Technical Data

Frequency band

433.0525 > 434.7900 Mhz

Channel space

12.5 kHz

Number of available on/off command max.

24 + Start and EMO

Hamming distance

≥ 15

Radio communication

bi-directional

Frequency handling

Automatic and dynamic switching between 2 channels

Power supply

LR6(AA)1.5V / NiMH(AA)1.2V x2

Stop command response time

~ 50 ms

Command response time

~ 50 ms

Protection degree

IP65

Operating and storage temperature

(-25°C)~(+55°C) / (-40°C)~(+85°C)

Housing material

PA6 (GF30%)



Accessories

Qi Charging Pad



K Series Hip Belt




K Series Transparent Pouch



K Series Lanyard



Applications





visit our website



Via Don Signini 43 - 28010 -
Briga Novarese - NO - ITALY
c.f. p.iva - 01179050032

tel. +39 0322 93574 / 953788
fax. +39 0322 953787
www.juukoitaly.it

K Series